

CLUTCH HEAD COUNTERSUNK WOODSCREWS

Countersunk head seats flush with material.

Clutch Head screws only operate in a clockwise direction, ideal for permanent fixtures.

Coarse thread woodscrew designed for screwing into timber.

Stocked in zinc plated steel.

No special tool required for installation, One-way Clutch Head screws are installed with flat blade screw driver.

LEVEL 3:
Maximum Security

Can be installed and removed with the following tools:

- Flat Blade Insert Bit
- Screwdriver
- Removal Tool

See page 135 - For more details on Driver Tools

10G

PART NO.	LENGTH	DRIVE SIZE	REMOVAL TOOL	HEAD DIA	HEAD HEIGHT	MATERIAL	\$/100
CHCW10G-Z	25mm	SLD8	RT51	9.3mm	5mm	Zinc Plated	\$39.50
CHCW10H-Z	32mm	SLD8	RT51	9.3mm	5mm	Zinc Plated	\$44.20
CHCW10I-Z	38mm	SLD8	RT51	9.3mm	5mm	Zinc Plated	\$51.70
CHCW10J-Z	50mm	SLD8	RT51	9.3mm	5mm	Zinc Plated	\$62.50

12G

PART NO.	LENGTH	DRIVE SIZE	REMOVAL TOOL	HEAD DIA	HEAD HEIGHT	MATERIAL	\$/100
CHCW12I-Z	38mm	SLD10	RT51	11mm	5.4mm	Zinc Plated	\$65.90
CHCW12J-Z	50mm	SLD10	RT51	11mm	5.4mm	Zinc Plated	\$83.70
CHCW12K-Z	63mm	SLD10	RT51	11mm	5.4mm	Zinc Plated	\$97.80
CHCW12L-Z	75mm	SLD10	RT51	11mm	5.4mm	Zinc Plated	\$130.30



We can supply broken packs; just add 20% to the price.
Contact Our Sales Team To Find Out More